

SAFETY DATA SHEET

Ribble Fuel Oils



Page: 1

Compilation date: 28/11/2014

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: INDUSTRIAL HEATING OIL 35

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: For use as heating fuel.

1.3. Details of the supplier of the safety data sheet

Company name: RIBBLE FUEL OILS

281 Carnfield Place

Walton Summit

Bamber Bridge

PRESTON

PR5 8AN

Tel: 01772 337367

Fax: 01772 620094

Email: info@ribblefueloils.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: Xn: R20; Xi: R38; Xn: R40; N: R51/53; Xn: R65

Classification under CLP: Carc. 2: H351; Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Skin Irrit. 2: H315; STOT RE 2: H373; Acute Tox. 3: H331

Most important adverse effects: Harmful by inhalation. Irritating to skin. Limited evidence of a carcinogenic effect. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Harmful: may cause lung damage if swallowed.

2.2. Label elements

Label elements under CLP:

Hazard statements: H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H331: Toxic if inhaled.

H351: Suspected of causing cancer.

H373: May cause damage to organs through prolonged or repeated exposure.

H411: Toxic to aquatic life with long lasting effects.

Signal words: Danger

Hazard pictograms: GHS08: Health hazard

SAFETY DATA SHEET

Ribble Fuel Oils



Page: 2

GHS09:

Environmental GHS07:

Exclamation mark



- Precautionary statements:** P260: Do not breathe fumes, vapours, spray.
P308+313: IF exposed or concerned: Get medical advice.
P280: Wear protective gloves, clothing and eye protection.
P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P331: Do NOT induce vomiting.
P311: Call a POISON CENTER or doctor.
P314: Get medical advice if you feel unwell.

Label elements under CHIP:

Hazard symbols: Harmful.

Dangerous for the environment.



- Risk phrases:** R20: Harmful by inhalation.
R38: Irritating to skin.
R40: Limited evidence of a carcinogenic effect.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65: Harmful: may cause lung damage if swallowed.
- Safety phrases:** S36/37: Wear suitable protective clothing and gloves.
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.
S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

LOW BOILING HYDROCARBON AND OXYGENATED HYDROCARBON FLUID

EINECS	CAS	CHIP Classification	CLP Classification	Percent
--------	-----	---------------------	--------------------	---------

SAFETY DATA SHEET

Ribble Fuel Oils



Page: 3

271-240-3	68526-92-1	Xn: R65	Asp. Tox. 1: H304; Aquatic Chronic 4: H413	30-50%
-----------	------------	---------	--	--------

DISTILLATE MARINE FUEL

269-822-7	68334-30-5	Xn: R40; Xn: R20; Xn: R65; Xi: R38; N: R51/53	Acute Tox. 4: H332; Aquatic Chronic 2: H411; Skin Irrit. 2: H315; Carc. 2: H351; STOT RE 2: H373; Asp. Tox. 1: H304	30-50%
-----------	------------	---	---	--------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash thoroughly with soap and water or a recognised skin cleanser. Remove contaminated clothing and laundry before re-use.

Eye contact: Flush eyes with water for several minutes. Remove contact lenses if present. If irritation or blurred vision occurs and persists, obtain medical attention.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Water fog. Alcohol or polymer foam. Dry chemical powder. Carbon dioxide. Use water spray to cool containers. DO NOT USE WATER JET

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates and gases including oxides of sulphur and nitrogen, carbon monoxide, carbon dioxide and unidentified organic compounds.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

[cont...]

SAFETY DATA SHEET

Ribble Fuel Oils 



Page: 4

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

LOW BOILING HYDROCARBON AND OXYGENATED HYDROCARBON FLUID

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	5mg/m ³	-	-	-

DISTILLATE MARINE FUEL

EU	5 mg/m ³	-	-	-
----	---------------------	---	---	---

[cont...]

SAFETY DATA SHEET

Ribble Fuel Oils 



Page: 5

DNEL/PNEC Values

Hazardous ingredients:

DISTILLATE MARINE FUEL

Type	Exposure	Value	Population	Effect
DNEL	Inhalation short term 15 mins	4300 mg/m ³	Workers	Systemic
DNEL	Inhalation long term 8 hrs TWA	68 mg/m ³	Workers	Systemic
DNEL	Dermal long term 8 hrs TWA	2.9 mg/kg	Workers	Systemic

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Yellow

Odour: Characteristic odour

Evaporation rate: Slow

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Kinematic viscosity: 2.5

Viscosity test method: Kinematic viscosity in 10⁻⁶ m²/s at 40°C (ISO 3104/3105)

Boiling point/range°C: 190

Flash point°C: 75

Relative density: 0.830

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

[cont...]

SAFETY DATA SHEET



10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates and gases including oxides of carbon and sulphur and unidentified organic and inorganic compounds.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

LOW BOILING HYDROCARBON AND OXYGENATED HYDROCARBON FLUID

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

DISTILLATE MARINE FUEL

DERMAL	Mouse	OECD 451 2 yrs	Positive	-
DERMAL	RBT	OECD 404	Irritation	-
EYES	RBT	OECD 405	Non-irritating	-
VAPOURS	RAT	4H LC50	4.1	mg/l

Relevant effects for mixture:

Effect	Route	Basis
Acute toxicity (harmful)	INH	Hazardous: calculated
Irritation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

SAFETY DATA SHEET



Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

LOW BOILING HYDROCARBON AND OXYGENATED HYDROCARBON FLUID

ALGAE	72H ErC50	>100	mg/l
Daphnia magna	48H EC50	Not toxic	-
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	>100	mg/l

DISTILLATE MARINE FUEL

ALGAE	72H ErL50	78	mg/l
DAPHNIA	48H EL50	68	mg/l
FISH	96H LC50	21	mg/l

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1202

14.2. UN proper shipping name

Shipping name: DIESEL FUEL

SAFETY DATA SHEET

Ribble Fuel Oils



Page: 8

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H331: Toxic if inhaled.

H332: Harmful if inhaled.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

H413: May cause long lasting harmful effects to aquatic life.

R20: Harmful by inhalation.

R38: Irritating to skin.

R40: Limited evidence of a carcinogenic effect.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

[cont...]

SAFETY DATA SHEET

Ribble Fuel Oils



Legend to abbreviations:

PNEC = predicted no effect level

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = physico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[final page]

inal page]